



Govt. corners identified = +, + . Corners of previous subd. surveys = X. Corners established on this survey = O

Description of Corners found, or established on this survey.

- |  |   |
|--|---|
| (1) Govt. stone, properly marked.  | (7) Govt. stone, properly mkd.  |
| (2) Sandstone, 18x12x7, chiseled 1/4; 6" span, scribed 1/4 RT. S. 60° W. 1.7 FT.         | (8) Govt. stone, properly mkd.  |
| (3) Post at fence cor.; 20" spruce scribed 1/4 RT. bears N35° W. 36.5 FT.                | (9) At corner fence post; missing Govt. 1/4 stone was in place and tied to the NE & NW. cors. of Sec. 14 in 1914 retracement survey by F.I.H. |
| (4) Stone 7x3 ins.; 13 ins. above ground. At fence corner.                               | (10)  |
| (5) Sandstone, 17x9x5 ins.; Chiseled GEN. 14; 7 pins, scribed 1/4 RT. S. 29° E. 11.7 FT. | (11)  |

**COUNTY SURVEYORS RECORD**  
GRAND COUNTY, COLORADO.

Survey by *Franklin C. Huntington* Co. Sur.  
For *Ted A. Engle*  
Date *June 17-18, 1930* Scale of Map *1" = 600 FT.*  
Courses *True* Var. *14° 30' E.*  
Measurements *400 FT. Tape*