



Govt. corners identified = +, + . Corners of previous subd. surveys = X. Corners established on this survey = O

Description of Corners found, or established on this survey.	
(1) Iron rod, 1" diam., 12" long, set 11" in ground.	(7) Set 3/8" iron rod, 20" long, 1.7" in ground, under R.O.W. fence
(2) 1 1/2" pipe, 3" above ground	(8) Set 3/8" iron rod, 18" long, 16" in ground, under R.O.W.
(3) Iron rod, 5/8" dia., sq. head, 2" above ground.	(9) 3/4" iron rods, 2" above ground.
(4) Iron rod, 5/8" dia., 18" long, set 16" in ground.	(10) Govt. metal post, properly marked.
(5) Old cor. plug - Replace iron rod, 5/8" dia., 20" long, set 18" in ground.	(11) Govt. metal post, properly marked.
(6) Set iron rod, 1 1/2" dia., 24" long, set 20" in ground.	(12)

COUNTY SURVEYORS RECORD
 GRAND COUNTY, COLORADO.
 Survey by *Frank J. Huntington* Co. Sur.
 For *Koppers Co.*
 Date *Nov. 4th 1923* Scale of Map *1" = 200'*
 Courses *TRUE* No. *1518E*
 Measurements *Steel Tapes*
 Instruments *Gurley transit*
 Assistants *Dan Bergquist & Roy Burak*